



THIẾT BỊ LỌC MIỀN NAM

CÔNG TY TNHH CÔNG NGHỆ THIẾT BỊ LỌC MIỀN NAM

Địa chỉ: Số 11, Đường 12, Phường 11, Gò Vấp, TP.HCM

Điện thoại: 028.3588.3699

AIR FILTER FRAME



GREENFILTER

Metal Mesh Filter

The frame is constructed of aluminum or stainless steel, easy to clean and use. Suitable for working in harsh environment.

Application

Primary filtration to remove moisture, oil residue or oil mist, grease,... in very dirty environments and general ventilation systems.

Ventilation conditions which require acid-base resistance air filters.

Feature

Washable for repeated use, cost efficient.

Ideal for high moisture, high temperature and acid resistant operating conditions.

Super low initial pressure drop.

High dust holding capacity.

Style	Pre Filter
Material	Aluminum, stainless steel
Frame	Galvanized wire, aluminum, stainless steel
Final recommended pressure drop	250Pa
Working temperature	200 – 300°C
Max temperature	350°C
Max humidity	100%
Filter efficiency	65% ≤ G2 < 80%
According EN 779:2012	80% ≤ G3 < 85%



Dimensions	Air flow (m³/h)	Classification EN779:2012	Face velocity	Initial pressure drop (Pa)	Final recommended pressure drop (Pa)	Filter area (m²)
592x592x22	3400	G1	2.5	10	250	0.35
592x490x22	2800	G1	2.5	10	250	0.29
592x287x22	1700	G1	2.5	10	250	0.17
592x592x46	3400	G2	2.5	10	250	0.35
592x490x46	2800	G2	2.5	10	250	0.29
592x287x46	1700	G2	2.5	10	250	0.17

